## ideal lux.



## **General** info

**DECORATIVO - Wall** 

Indoor wall mounted adjustable lamp with multiple sources, in-built switch and diffuse and direct light emission



 Installation
 Wall

 Guarantee
 5 years

 Gross weight
 2.02 kg

 Volume
 0.016576 m³



## Technical info

Net weight1.41 kgInsulation classIProtection indexIP20Operating temperature $0^{\circ} \sim +40 \,^{\circ}\text{C}$ 

DimmerNon-dimmable, On-OffPower output100-240 V AC 50/60 HzPower supplyIn-built, included

YES (by qualified operators only), electronic

Adjustability YES



## Source info

Useful light flux

Integrated source Light bulb (not included), Integrated LED

module

Repleaceable source YES (LED: by qualified operators only)

**Power** E27/LED max 1 x 60W / 1.5W

 Emission
 Diffuse + Direct

 Max consuption
 max 60W / LED 1.5 W

 Features LED
 LED SMD BRIDGELUX

 CCT
 3000 K

 Duration LED (t. 25°c)
 20000 h

 CRI
 > 80

 Light beam
 23°

 Light beam flux
 55 lm

Photobiological risk 2

Standby power < 0.50

Bulb included LED INTEGRATO LED 55Lm 3000K

LED 45 lm